




CBSLH-24V-F-3M | DATASHEET

Illumination cable, side A flying leads, side B SM 3 way female connector, 24V - 3m



Opto Engineering® provides various kinds of cables to match our offer of illuminators, optics, cameras and accessories.

All the cables we offer meet industrial standards of robustness and durability.



SPECIFICATIONS

Electrical specifications

Type		Power
Number of poles		2
Conductor cross section	(AWG)	24
Cable diameter	(mm)	3.5
Cable length	(m)	3
Cable insulation material		PVC
Shield		No
Bending cycles	(cycles)	-
Minimum bending radius	(mm)	14
Side 1		JST SM 3 way female connector
Side 2		Flying leads
Other		-
Voltage rating	(VDC)	24
Current rating	(A)	2

Environment

Operating temperature	(°C)	-25-+80
-----------------------	------	---------

COMPATIBLE PRODUCTS


Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.

CONNECTOR PINOUT



Pin	Function	Cable color
1	LED +	Red
2	-	-
3	LED -	White

Cable side