

LTICGR1000-D1 | DATASHEET

Analogue lighting controller unit, 1 channel, 24V, 2A, constant mode, power adaptor 24V plug



Opto Engineering® offers light intensity controllers available as accessories to precisely adjust the light intensity of our wide range of lights.



SPECIFICATIONS

Electrical specifications

Light control type		Analog (knob)
Operating mode		Continuous
Status LEDs		No
Supply voltage	(V)	24 DC
Input		-
Output channels		1, constant current
Output voltage	(V)	24
Max output current	(A)	2
Max output power	(W)	48
Output		-
Power cord		Not included

Mechanical specifications

Width	(mm)	24
Length	(mm)	55
Height	(mm)	90
Mass	(g)	140
Mounting		DIN rail

Environment Specification

Operating temperature	(°C)	0-40
Storage temperature	(°C)	0-50
Operating relative humidity	(%)	20-85, non condensing
IP rating		IP20
Installation		Indoor use only

COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.