


LTZGK070-15-2-UV375-24V

Lighting Dimension



Mechanical Information

Casing Material	Aluminium
Storage Temperature Range	0 - 45°C
Storage Humidity Range	20 - 85%
Weight	103g
Length / Outer Diameter	70mm
Width / Inner Diameter	32mm
Thickness / Height	20.5mm

ILLUMINATOR DATA

LTZGK070-15-2-UV375-24V

Lighting Information			
Part Number	LTZGK070-15-2-UV375-24V		
LED Color	UV375		
Wavelength	375nm		
Working Distance	75 mm	85 mm	95 mm
Intensity (±15%)	-	-	-
Illumination (number of row)	2		
Illumination Active Area	Active Length / Outer Dia.		62 mm
	Active Width / Inner Dia.		37 mm
Emission angle	15		
Eye Safety Class (IEC62471)	EXEMPT		
Chromaticity Table For White colour only	Nil		

Electrical Information	
Rated Constant Voltage	24V±2%
Rated Constant Current	180mA
Power Consumption	4.32W
Casing temperature, After 60 minutes operation	52.6 °C

Strobe Mode Specification		
*Normal Strobe Voltage	24 V	
*Normal Strobe Current	180 mA	
Overdrive Voltage Range	Min: 36V	Max: 48V
Overdrive Current Range	Min: 0.64 A	Max: 0.72 A
Recommended Overdrive Voltage	36V	
**Max. Trigger Pulse Duration	10 msec	
**Max. Duty Cycle	10%	

*Normal strobe means the lighting is operated using the rated power. Overdrive means the power supplied to the lighting exceeded the rated power.

**Overdrive condition must not exceed the max. trigger pulse duration and max. duty cycle.

ILLUMINATOR DATA

LTZGK070-15-2-UV375-24V

Connection Information			
Connector Type (Default)	JST SMR-03V		
Cable Length	50 cm		
Pin Configuration 	Pin	Signal	Cable Colour
	1	LED +	Red
	2	N.C	-
	3	LED -	White
			

Additional Information	
Additional Cooling Method	Attached to machine part for better heat dissipation
Intensity Controller Selection	SD, ST, ANG, LC, SDA, SDP series
CE Conformity	YES
RoHS Compliance	YES

Application	
Illumination Type	UV Illumination
Application Use	Allow Chemicals That Has UV Lighting Interaction to be Visible Under The Blue Light

ILLUMINATOR DATA

LTZGK070-15-2-UV375-24V

Lighting Pattern				
Working Distance	For further details please contact us.			
Display and Image				
Data Results	Horizontal	Meas.(mm)	Vertical	Meas.(mm)
	90%		90%	
	80%		80%	
	70%		70%	
	60%		60%	
	50%		50%	
	40%		40%	
	30%		30%	
	20%		20%	
	10%		10%	